


CW - 898

Free standing

Water Dispenser Operation Manual




Contents	Page
Preface / Parts	1
Piping Installation	2
Cup Holder Instruction	3
CO ₂ Cylinder Installation	4
Cold Operation Method	5
Hot Operation Method	6
Soda Operation Method	7
Safety Reminder	8
Container Instruction	9
cleaning & Maintenance	10
Problem Shoot	11-12

Please read these instructions completely before operating this unit


PREFACE / PARTS

Before using this machine, we advise you to read this manual thoroughly.
Please follow the instructions for proper operation to prevent risk or damage.




PIPING INSTALLATION

1. Disassemble the original water tap, then put on the tri-way socket and inlet ball valve. See drawing (A).




drawing (A)

2. Connect the 1/4" PE water pipe between inlet ball valve and inlet connector. See drawing (B).




CUP HOLDER INSTRUCTION


1. Push the clip on top of the cup holder lid as the arrow A is showing.




2. Hold the clip as shown in the picture by arrow 1, then lift up the lid as directed from arrow 2.



3. Please load the cups into the cup holder with bottoms up. Push cups all the way down as the arrow is showing till no more may fit in.





4. Simply pull out the cups gently when needed.




CO₂ CYLINDER INSTALLATION

Please prepare a pressure regulator, adopter and CO₂ bottle. Connect the pressure regulator to the CO₂ bottle with the adopter. After that, apply the PE pipe (CO₂ refill tube) to connect the pressure regulator and soda machine.

Remark : Please adopt the pressure under 4 bar / 4 KG.



COLD OPERATION METHOD




1. Ensure the power switches at rear panel are OFF, then plug in the power cord and connect inlet water.

2. Press ambient or cold water (if there is no ambient water option) button to dispense some water to flush filters. This is important to ensure

3. Touch and hold cold water button to dispensed water until water comes out, it may take 1 - 2 minutes.

4. Turn on cold power switch at back, the machine will start chilling immediately. The chilling may need up to 40 minutes.



For security reasons, the dispensing is limited within 60 seconds. If you need more water please touch button again.



Cold Water



Hot Water



Sparkling Water



Ambient Water

HOT OPERATION METHOD

1. Ensure the power switches at rear panel are OFF, then plug in the power cord and connect inlet water.
2. Press ambient or cold water (if there is no ambient water option) button to dispense some water to flush filters. This is important to ensure drinking water quality.
3. Press and hold hot water button until seeing water comes out.

Note: This is very important to prevent hot tank dry-heat.

Based on safety reasons, each time pressing unlock button, hot water button must be pressed for 3 seconds to dispense hot water. After the first dispense, hot water may be dispensed right away during the same unlocking period.

4. Turn on hot power switch at back, the machine will start heating immediately. The reheating will be started automatically when hot water temperature is too low.

For secure reason, the dispensing is limited within 60 seconds. If you need more water please touch button again.



Cold Water




Hot Water



Sparkling Water



Ambient Water



SODA OPERATION METHOD

1. Press ambient or cold water (if there is no ambient water option) button to dispense some water to flush filters. This is important to ensure drinking water quality.
2. Turn on the soda power switch at back, then press any button to allow mains water filling into soda tank.
3. Please push the soda water button to drain out the primary soda water in the tank. The newly produced soda water is now ready to drink.

For secure reason, the dispensing is limited within 60 seconds. If you need more water please touch button again.



Cold Water





Hot Water




Sparkling Water




Ambient Water




SAFETY REMINDER



Leave a space no less than 15cm between the wall and dispenser .




Keep the machine away from sunlight , heat , and wetness .





Be sure to use single outlet socket with correct power voltage . Plug the power cord directly into electrical socket .

CONTAINER INSTRUCTION




When the float rises higher than the drip tray, as shown in Drawing (A), the drain container is nearly full and must be emptied immediately. The procedures are as follows:

1. Open the front lower cover, hold the container and turn the container buckle in clockwise direction to aligned with the triangle sign for open. Pull down the container and pour out the water.
2. After emptying the container, insert the opening to the container buckle and turn the buckle in counterclockwise direction to aligned with the triangle sign for close. Make sure the container is completely attached to the buckle to prevent it from falling off.





CLEANING & MAINTENANCE



1. Please make sure the machine is completely disconnected from electricity before cleaning.

2. Remove the caps on top of the hot water and cold water drains. The remaining water in the tanks will drain out. Cleaning may start when both tanks are emptied. Please put the caps back when cleaning is done.



Caution: For your safety, please contact your distributor or qualified technician for repair when the water dispenser is damaged.

PROBLEM SHOOT

Defection Status	Possible Defection Reason	Solution
Hot water is not hot	1. The hot power switch is off.	Turn the hot power switch on.
	2. Hot temperature protection is enabled due to dry-heat.	Call for service to reset the protection button on the hot tank.
	3. Problem with PCB or thermostat.	Please contact service people.
No hot water	1. No water from mains water supply.	Check inlet water supply.
	2. Inlet water pressure is too low.	Check inlet water pressure from pre-filtration system or water supply.
	3. Water is not being filling into hot tank.	Please press hot water button to fill water into hot tank until water comes out.
Cold water is no cold	1. The cold power switch at back is off	Turn the cold power switch on.
	2. Chilling time is not enough.	Please wait 40 minutes for water chilling.
	3. Refrigerant leaks.	Contact service people.
No cold water	1. No water from mains water supply.	Check inlet water supply.
	2. Cold water is being filling into cold tank.	Contact the service people.
	3. Inlet water pressure is too low.	Check inlet water pressure from pre-filtration system or water supply.
	4. Water in cold water tank got frozen.	Unplug the power cord then wait for 4 – 8 hours. Internal pipe may be broken please contact service people as well.
No sparkling water	1. CO ₂ runs out.	Replace a new CO ₂ Cylinder.
	2. The soda power switch at back is off.	Turn the soda power switch on.
	3. Water is unable to be filled to sparkling water tank.	Contact the service people.

PROBLEM SHOOT

Defection Status	Possible Defection Reason	Solution
Hot water is dripping from dispensing nozzle.	1. Inlet water pressure is too low.	Check inlet water pressure from pre-filtration system or water supply.
	2. The solenoid valve got malfunction.	Contact service people.
Sparkling water is dripping from dispensing nozzle.	1. The remaining sparkling water in pipe is flowing due to CO ₂	Wait for a few seconds, it will be stopped.
	2. The solenoid valve got malfunction.	Contact service people.
UV indicator light is blinking and hearing beeps when dispensing water.	1. UV lamp is failure or no UV lamp is connected	Replace a UV lamp or check if the UV wire is disconnected.
	2. UV board is failure.	Contact service people.
All dispensing buttons are blinking and hearing beeps when press button.	1. There is leakage detected inside of water dispenser.	Unplug the power cord, then dry water on the internal base or ask for service.
	2. The waste water container is full.	Please drain all water from waste water container.
Bubble of sparkling water is insufficient.	1. The CO ₂ and water doesn't mixed properly.	Please wait more time.
	2. CO ₂ almost runs out.	Replace CO ₂ cylinder
	3. CO ₂ output pressure is too low.	Please adjust output pressure to 4 bar as suggestion.